

Amendments to the Claims:

Please amend Claims 4, 6, 9, 15, and 20 to read, as follows.

1. **(Canceled)**

2. **(Canceled)**

3. **(Canceled)**

4. **(Currently Amended)** A developing apparatus comprising:  
a developer bearing member; and  
a developer carrying screw placed in parallel with said developer bearing member,  
wherein said developer carrying screw includes a rotary shaft and a spiral blade,  
and said spiral blade is wound about said rotary shaft in a spiral form and has a carrying  
surface for carrying developer, and

[[and]] wherein when viewing said developer carrying screw in cross-section in a  
longitudinal direction of said developer carrying screw, an inclination angle with respect to  
a rotation center line of said rotary shaft at one side of said carrying surface is smaller than  
an inclination angle with respect to a rotation center line of [[at]] an opposite side of said  
carrying surface.

5. **(Original)** The developing apparatus according to claim 4,  
wherein said developer carrying screw is placed adjacently to said developer  
bearing member.

6. **(Currently Amended)** A developing apparatus comprising:  
a developer bearing member; and  
a developer carrying screw placed in parallel with said developer bearing member,  
wherein said developer carrying screw includes a rotary shaft and a spiral blade,  
and ~~wherein~~ said spiral blade is wound about said rotary shaft in a spiral form and has a  
carrying surface for carrying a developer, and

[[and]] wherein when viewing said developer carrying screw in cross-section in a  
longitudinal direction of said developer carrying screw, said carrying surface has surface  
portions having a plurality of different inclination angles with respect to a rotation center  
line of said rotary shaft.

7. **(Previously Presented)** The developing apparatus according to claim 6,  
wherein a portion of said carrying surface near to said rotary shaft has a smaller  
angle than a portion of said carrying surface farther from said rotary shaft.

8. **(Previously Presented)** The developing apparatus according to claim 6,  
wherein when a distance from a reference surface of said rotary shaft to a tip end of  
said blade is  $H1$ , and a distance from the reference surface to a point P at which the  
plurality of carrying surfaces intersect each other is  $H2$ ,

$$H2 < H1 \times \frac{1}{2} \text{ is satisfied.}$$

9. **(Currently Amended)** The developing apparatus according to claim 8,

wherein ~~wherein~~:  $H1 \times \frac{1}{3} < H2 < H1 \times \frac{1}{2}$  is satisfied.

10. **(Previously Presented)** The developing apparatus according to claim 9,  
wherein an inclination angle of said portion of said carrying surface near to said  
rotary shaft is equal to or more than 3 degrees and equal to or less than 50 degrees.

11. **(Original)** The developing apparatus according to claim 6,  
wherein said developer carrying screw is placed adjacently to said developer  
bearing member.

12. **(Canceled)**

13. **(Canceled)**

14. **(Canceled)**

15. **(Currently Amended)** A developing apparatus comprising:  
a developer bearing member; and  
a developer carrying screw placed in parallel with said developer bearing member,  
wherein said developer carrying screw includes a rotary shaft and a plurality of  
spiral blades, and ~~wherein~~ each of said plurality of blades is wound about said rotary shaft  
in a spiral form and has a carrying surface for carrying a developer, and

[[and]] wherein when viewing each of said plurality of developer carrying screws in  
cross-section in a longitudinal direction of each of said plurality of developer carrying  
screws, an inclination angle of a carrying surface of each one of said plurality of blades  
with respect to a rotation center line of said rotary shaft is different from the inclination  
angles of the carrying surfaces of the other blades.

16. **(Previously Presented)** The developing apparatus according to claim 15,  
wherein each of said plurality of said developer carrying screws includes a first  
blade with an inclination angle of a carrying surface having a first value, and a second  
blade with an inclination angle of a carrying surface having a second value smaller than the  
first value, and said second blade is adjacent to said first blade, at an upstream side in a  
developer carrying direction.

17. **(Previously Presented)** The developing apparatus according to claim 16,  
wherein when a distance from a reference surface of said rotary shaft to a tip end of  
said first blade is H1, and a distance from the reference surface to a tip end of said second  
blade is H2,

$$H2 < H1 \times \frac{1}{2} \text{ is satisfied.}$$

18. **(Previously Presented)** The developing apparatus according to claim 17,  
wherein an inclination angle of said first blade is larger than 60 degrees, and an  
inclination angle of said second blade is larger than 5 degrees and smaller than 40 degrees.

19. **(Previously Presented)** The developing apparatus according to claim 16,  
wherein a surface in a space between said second blade and said first blade at an  
upstream side of said second blade in a developer carrying direction is inclined with  
respect to the developer carrying direction.

20. **(Currently Amended)** The developing apparatus according to claim 19,  
wherein when a distance from a reference surface of said rotary shaft to a tip end of  
said first blade is H1, and a distance from the reference surface to a point P at which the  
carrying surface of said first blade and the surface in the space are intersecting each other is  
H3, satisfies:

$$H3 < H1 \times \frac{1}{2} \text{ is satisfied.}$$

21. **(Original)** The developing apparatus according to claim 20,  
wherein an inclination angle of the surface in the space is larger than 5 degrees and  
smaller than 40 degrees.

22. **(Original)** The developing apparatus according to claim 15,  
wherein said developer carrying screw is placed adjacently to said developer  
bearing member.

23. **(Previously Presented)** The developing apparatus according to claim 4,  
wherein the inclination angle of the carrying surface is equal to or more than 50  
degrees and equal to or less than 60 degrees.

24. **(Previously Presented)** The developing apparatus according to claim 6,  
wherein the carrying surface is a curved surface.